

Series Comparison				
	1000 series	2000 series	3000 series	5000 series
Mail Users	Up to 50	Up to 500	Up to 1,500	Up to 10,000
Internal Load Balancing *	-	+	+	+
Inspected Protocols	SMTP, POP3			
Mail Services Protocols	ESMTP/S with LDAP Authentication support, POP3/S, IMAP4/S, WebAccess**			
Mail Delivery Protocols	SMTP/S, POP3 Pull-mode and Local**			
Anti-Virus Engines	F-Secure [®] , Zero-Hour [™] and a Heuristic engine by PineApp			
Anti-Spam Engines	11 layers including: Commtouch RPD [™] , RBL, Zombie Detection, Pattern recognition, Bayesian & Rules, IP Reputation			
Disk Size	80GB IDE	80GB PATA	160GB SATA	2X72GB SAS
Network Interfaces	1XGbE	4x10/100Mbps	4XGbE	4XGbE
Dimension (W x D x H)	31x35.8x8.75 cm (12.2x14.1x3.4 inch)	42.9x36x4.4 cm (16.9x14.2x1.7 inch)	44.3x38.1x4.4 cm (17.4x15x1.7 inch)	43.2x61x4.4 cm (17x24x1.7 inch)
Certifications	FCC, CE, UL, CUL, CB	FCC, CE, LUV, RoHS	FCC, CE, LUV, RoHS	CE, CB, LUV, FCC, UL, RoHS
Warranty	1 year limited warranty			
Licensing	Revolutionary unlimited user licensing program			
* Achieved by adding an additional unit. ** When Acting as Mail Server.				